

275kVA Cummins OzPower



ENGINE

MANUFACTURER	Cummins Diesel
ENGINE MODEL	6CTAA8.9G2
TYPE/CYLINDER	4 Stroke - 6 L, Turbocharged Aftercooled
FUEL CONSUMPTION	53 L @ 100 % Load
COOLANT CAPACITY	18 L
GOVERNOR	Electronic
CUBIC CAPACITY	8.9 L
FREQUENCY	50 Hz

ALTERNATOR

AC	Brushless
ALTERNATOR BRAND	OEM AVR Controlled
THF	Less than 5%
PROTECTION CLASS	IP23
INSULATION CLASS	Class H

SPEED	POWER		NOISE LEVEL	FUEL RUN TIME	PRIME OUTPUT
	Standby Power		dBA @7m see *1		
	kW	kVA	dBA		
1500RPM	220	275	71.9	24 hrs	250kVA

DIMENSIONS

LENGTH	3.5m
WIDTH	1.08m
HEIGHT	2.12m
WEIGHT	3121kg

CANOPY

- Bunded fuel tank with fork lift pockets and skid tie down points
- Centre lift, lockable doors with control panel viewing window
- Heavy duty powder coat finish white canopy with a black base
- Emergency Stop - External

OPTIONS

- Outlets - 1 x 32 AMP 3 Phase / 2 x 15 AMP Single
- Phase Weatherproof IP66

CONTROLS

- Controller - SmartGen 6120 with LCD Display
- Circuit Breaker - Moulded Case 3 Pole
- Battery Isolator - Fitted with Canopy Adjacent Battery