

DGPL375C-3

50 Hz @ 1500rpm, 3-phase /
4-wiring

350kVA
CUMMINS
DGPL350C-3

A. STANDARDS & CONDITIONS

Design Standards

The designs and the productions are in conformity with:

- Conformance Europeenne (CE)
- China Compulsory Certification (CCC)
- ISO8528-5:2005
- GB/T2820.5-2009
- AS 3000-1997
- AS 3010.1-1988

Environmental Operating Conditions

- Installation place: Outdoors or indoors (well ventilated)
- Ambient temperature: -25°C to 50°C. The coolant heater is needed when the temperature is below 5°C
- Humidity: Less than 90%
- Altitude: Below one thousand (1000) meters above sea level

Factory Inspection

- Inspection items
- Protection devices working test
- Starting ability in normal temperature
- 50% rated power load moment capability
- Voltage deviation and speed varying: 0%, 25%, 50%, 75%, 100%, 110% Load

Painting Process


- Painting process specifications and colors are based on the manufacturer's standard
- The customer could also choose the color which the manufacturer offers

B. GENERAL FEATURES

- Cummins engine NTA855-G4
- Close coupled to a Stamford alternator HCI444E
- Microprocessor control module PLC-7420
- ABB main circuit breaker: 630A
- Rotate speed governor: Electrical governor
- Excitation System: Self Excited, SHUNT
- A.V.R. Model: AS440
- Key switch
- Emergency stop switch
- ATS (automatic transfer switch) receptacle
- Remote run connector
- 2x12V/120AH sealed for life maintenance free battery
- Lockable battery isolator switch
- Powder coated canopy
- 50°C radiator
- Oil pump on the engine
- Non-returning valve for fuel inlet hose of the engine
- Steel base frame with forkslots

- Vibration isolators between the engine/alternator and base frame
- Dry type air filter
- Base fuel tank for 21 hours running
- Drain points for fuel tank
- Breather valve for fuel tank
- Operation Manual / Specifications

C. GENERAL TECHNICAL DATA




1000023424-AP1-C6

MODEL	DGPL350C-3
STRUCTURE TYPE	R
TANK CAPACITY	1650 L
DRY WEIGHT	4790 kg
NOISE LEVEL @ 7M	75.7 dBA
DIMENSIONS	4242 x 1423 x 2426 mm
STANDBY POWER	385 kVA / 308 kW
PRIME POWER	350 kVA / 280 kW
VOLTAGE/AMPERE	415 V / 486.9 A

GENSET FUEL CONSUMPTION					
Freq./Load	25%	50%	75%	100%	110%
50Hz (L/h)	21	39	57	76	84

DIESEL GENERATION AUSTRALIA

DIESEL ENGINE




ENGINE SPECIFICATIONS

1000079858-AP1-A3

1	ENGINE MANUFACTURER/BRAND	Cummins
2	ENGINE MODEL	NTA855-G4
3	DIMENSIONS	N/A
4	DRY WEIGHT (APPROX.)	1410 kg
5	NUMBER OF CYLINDERS	6
6	BORE	140 mm
7	STROKE	152 mm
8	DISPLACEMENT (LITER)	14 L
9	COMPRESSION RATIO	14
10	TYPE OF INJECTION	Direct Injection
11	INTAKE SYSTEM	Turbocharged,water-to-air charge cooled
12	INTAKE RESISTANCE	6.2 kPa
13	COOLING SYSTEM	Water Cooled
14	FAN	Pusher
15	BATTERY VOLTAGE	24V
16	TYPE OF FUEL	No.2-D per ASTM D975
17	TYPE OF OIL	API CD/SE or CCMCD4
18	OIL CAPACITY	38.6 L
19	TYPE OF COOLANT	Glycol Mixture
20	COOLANT CAPACITY	60.6 L
21	BACK PRESSURE	10 kPa
22	STANDBY POWER	351 kW
23	PRIME POWER	317 kW
24	FUEL CONSUMPTION (100% LOAD)	197 g/kWh

DIESEL GENERATION AUSTRALIA

ALTERNATOR




1000069692-AP1-A1

ALTERNATOR SPECIFICATIONS

1	ALTERNATOR MANUFACTURER/BRAND	Stamford
2	ALTERNATOR MODEL	HCI444E
3	EXCITER	Brushless
4	COOLING FAN	Cast Alloy Aluminum
5	WINDINGS	100% Copper
6	INSULATION CLASS	H
7	WINDING PITCH	2 / 3
8	TERMINALS	12
9	DRIP PROOF	IP23
10	ALTITUDE	≤ 1000m
11	OVERSPEED	2250rpm
12	AIR FLOW	0.11m³/s(50Hz),0.135m³/s(60Hz)
13	VOLTAGE REGULATION	± 0.5%
14	TOTAL HARMONING TGH / THCat No Load < 1.5%	on load < 5%
15	TELEPHONE INTERFERENCE	THF < 2%; TIF <50

PLC-7420 CONTROL SYSTEM





1000177378-AP1-D3

PLC-7420 is an advanced control module based on microprocessor, containing all necessary functions for protection of the genset and the breaker control. It can monitor the mains supply, and automatically start the engine when the mains is abnormal. Accurately measure various operational parameters and display all values and alarms information on the LCD. In addition, the control module can automatically shut down the engine and indicate the engine failure.

- Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the mains supply and genset
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections; multiple parameters display, like pressure, temp. etc.
- Manual, automatic and remote work mode selectable
- Real time clock for time and date display, overall runtime display, 250 log entries
- Overall power output display
- Integral speed/frequency detecting, telling status of start, rated operation, overspeed etc.
- Communication with PC via RS485 OR RS232 interface, using MODBUS protocol



D. OVERALL DIMENSION

Dry weight	4786kg
Fuel tank capacity	1650L
Dimensions L x W x H	4242x1423x2426mm




- ⑧ Emergency stop switch
- ⑦ Air inlet
- ⑥ Access door
- ⑤ Exhaust gas outlet
- ④ Fuel drain
- ③ Tie down
- ② Base frame
- ① Control cabinet
- ⑬ Fuel inlet
- ⑫ Fork lift channel
- ⑪ Lifting lug
- ⑩ Roping lug
- ⑭ Cable trench
- ⑮ Coolant/Oil drain hose fitting
- ⑯ External fuel inlet/return hose fitting


DIMENSIONS	4242 x 1423 x 2426 mm
DRY WEIGHT	4790 kg



E. CONTROL SYSTEM



Control & Field wiring cabinet



Control module

Ref.	Description
1	Mains Input Changeover Switch
2	Control Cabinet Lamp Switch
3	Key Switch
4	Charge Indicator
5	Control Cabinet Lamp
6	Control Module
7	Limit Switch
8	ATS Connector
9	Remote Run Connector
10	Live Wire Terminals
11	Neutral Wire Terminal
12	Main Circuit Breaker
13	Emergency Stop Switch

a.	Button (next page)
b.	Button (increase value / previous item)
c.	Button (accept)
d.	Button (previous page)
e.	Button (decrease value / next item)
f.	Button (transfer the load to the mains supply, when in Manual)
g.	Mains supply available LED
h.	Stop / Reset Button
i.	Manual button (manual control mode)
j.	Mains supply on load LED
k.	Test button (test mode)
l.	Auto button (auto mode)
m.	Genset on load LED
n.	Mute / Lamp test button
o.	Start button (manual)
p.	Genset available LED
q.	Button (transfer the load to the genset, when in manual mode)
r.	Alarm LED (4 alarm items)
s.	LCD Display
t.	Control Module Name

1000023424-E3-E

10.2020