

DIESEL GENERATION AUSTRALIA

GYD5000E Mine Spec

6.5kVA Yanmar

6.5kVA **GYD5000E**

TECHNICAL

| MODEL | GYD5000E – Mine Spec | MANUFACTURER | Yanmar |
|---------------|----------------------|---------------|--------|
| ТҮРЕ | Portable | FUEL | Diesel |
| PHASE/VOLTAGE | 1/240 | TANK CAPACITY | 5.5 L |
| FREQUENCY | 50Hz | OIL CAPACITY | 1.65 L |
| SPEED | 3000RPM | ТҮРЕ | O.H.V |





CONTROLS

ENGINE

| KEY START | Engine Protection Oil Pressure |
|--------------------|--------------------------------|
| EMERGENCY STOP | Fitted |
| OPTIONS WHEEL KITS | Two Wheel or Four Wheel |
| BMA CERTIFICATION | Optional |

| Speed | POW | ER | NOISE LEVEL | RUN | START |
|---------|--------------------|-----|-------------------|-----------------|-------------------|
| | Max Output @ 0.8pf | | dBA @7m see *1 | TIME | |
| | kW | kVA | dBA | @ 100% / @ 75% | Recoil & Electric |
| 3000RPM | 5.0 | 6.5 | 80 | 2.8hrs / 3.6hrs | Recoil & Electric |

ALTERNATOR

| ALTERNATOR BRAND | Mecc Alte |
|---------------------|--------------|
| ТҮРЕ | Brushless |
| HARMONIC DISTORTION | Less than 5% |
| PROTECTION CLASS | IP 23 |
| INSULATION CLASS | Class H |

DIMENSIONS & WEIGHT

| LENGTH | 85cm |
|--------|-------|
| WIDTH | 55cm |
| HEIGHT | 60cm |
| WEIGHT | 105kg |

MINE SPEC INCLUSIONS

| LOCKABLE ISOLATORS | Battery, Starter & Control Panel |
|--------------------|----------------------------------|
| RCD 30ma | Fitted to Outlets |
| FIRE EXTINGUISHER | 1kg |
| JUMP START | Anderson Plug |
| BUNDED TRAY | Included |
| CENTRE LIFT | Included |
| EARTH STAKE | Included |
| OUTLETS | 10amp or 15amp IP66 C/B RCD |

