

GSW65P-P - 65kVA Pramac

**65kVA
PRAMAC
G S W 6 5 P - P**



TECHNICAL

MODEL 1103A-33TG2

FREQUENCY HZ 50

PHASE Three Phase

VOLTAGE 400 V

POWER FACTOR 0.8 cos

ENGINE

MANUFACTURER Perkins

ENGINE MODEL 1103A-33TG2

ENGINE COOLING SYSTEM Water

DISPLACEMENT 3300 cc

SPEED GOVERNOR Mechanical

FUEL Diesel

ASPIRATION Turbocharged

OIL CAPACITY 8.3 L

Standby Power LTP	POWER		NOISE LEVEL	FUEL CONSUMPTION	START
	Standby Power LTP Prime Power LTP		dBA @7m		
	kW	kVA	dBA	@ 75%	Electric
63kVA	50 48	63 60	67	10.4 L/h	Electric

BASE FRAME MADE OF WELDER STEEL PROFILE, COMPLETE WITH

- Anti-vibration mountings properly sized
- Welded support legs

PLASTIC FUEL TANK, COMPLETE WITH:

- Filler neck
- Air breather (ventilation pipe)
- Minimum fuel level sensor

OIL DRAININ PIPE WITH CAP:

- Oil draining facilities

DIMENSIONS & WEIGHT

LENGTH 2285mm

WIDTH 920mm

HEIGHT 1465mm

WEIGHT 1114kg

CANOPY:

- Soundproof canopy made up of modular panels, realized with zinc coated steel as treatment against corrosion and aggressive conditions, properly fixed and sealed allowing a full weatherproof enclosure.
- Easy access to the genset for maintenance purposes thanks to: Wide lateral access doors fixed by stainless steel hinges and provided with plastic lockable handles and internal perforated galvanized steel-sheet; Detachable panels, with screws holes protected by rubber tap.

SOUNDPROOF:

- Noise attenuation thanks to soundproofing material (polyurethane foam) and efficient residential silencer placed inside the canopy