

DIESEL GENERATION AUSTRALIA

DGLGL19

50Hz 1500RPM 14kW/17.5kVA

50Hz

General Features

- Engine 4TNV88-GGHWC YANMAR
- Alternator TAL-A40-F LEROY SOMER
- Controller DSE4620 DEEPSEA

Prime power	14kW/17.5kVA
Standby power	15kW/19kVA



- Electric speed control
- 12V starting batteries, maintenance-free type, connecting cables
- Equipped with ABB MCCB
- Equipped with industrial silencer and flexible exhaust hose
- Radiator 40°C max, fans are driven by belt with safety guard
- Base fuel tank: 24hour bunded fuel tank
- 12V charge Alternator
- Australia socket with RCBO
- Equipped with battery charger
- Design comply to ISO8528/GB2820
- Absorber (anti instant braking)
- User manual, Packing list

General Ratings

Voltage	Power				Frequency (Hz)	Phase	P.F (COSφ)	Prime Current (A)
	Prime kw	kva	Standby kw	kva				
415/240V	14	17.5	15	19	50	3	0.8	26.1

Prime power

This rating is for the supply of continuous electrical power at variable load. A 10% overload capability is available for a period of 1 hour within each 12-hour period of operation.

Standby power

This rating is for the supply of continuous electrical power at variable load in the event of utility power failure. No overload is permitted.

Dimension And Weight



Silent with Canopy
 Size(L×W×H): 1850×800×1400(mm)
 N.W.: 860 (kgs)

DIESEL GENERATION AUSTRALIA

DGLGYL19

50Hz 1500RPM 14kW/17.5kVA

50Hz

Engine Specifications

1	Engine model	4TNV88-GGHWC
2	Engine manufacturer	YANMAR
3	Number of cylinders	4
4	Cylinder arrangement	Vertical in line
5	Cycle	4 stroke
6	Aspiration	Naturally
7	Bore×Stroke(mm×mm)	88*90
8	Displacement (Liter)	1.995
9	Compression Ratio	19.1:1
10	Prime power/speed (kW/RPM)	18/1500RPM
11	Standby power/speed (kW/RPM)	16.4/1500RPM
12	Speed governor	Mechanical
13	Cooling system	Water-cooled
14	Coolant capacity (engine only) (L)	2.7
15	Steady speed droop (%)	≤ 5%
16	Total lubrication system capacity (L)	7.4
17	Oil consumption (% of fuel)	<0.15%
18	Fuel consumption at 100% load (L/H)	3.0
19	Starter motor	DC 12V/12.KW

Alternator Specifications

Compliance with GB755,BS5000,VDE0530,NEMAMG1-22,IED34-1,CSA22.2 and AS1359

1	Alternator model	TAL-A40-F
2	Alternator manufacturer	LEROYSOMER
3	Exciter type	Single bearing, Brushless, Self-excited
4	Rated output prime power	20kVA
5	Rated speed	1500 RPM
6	Rated frequency	50 Hz
7	Phase	3
8	Rated voltage	415V
9	Power factor	0.8
10	Voltage adjust range	≥5%
11	Voltage regulation NL-FL	≤±1%
12	Insulation grade	H
13	Protection grade	IP23

Main Electrical Performance Data


Stable Regulation rate	Fluctuation	Voltage			Frequency			Fluctuation
		Recover time	Instantaneous Regulating rate	Regulating rate	Stable regulation rate	Instantaneous regulating rate	Recover time	
+/-2.5%	0.5%	1.5s	+20%/-15%		+5%	+/-10%	5S	0.5%

DGLGL19

50Hz 1500RPM 14kW/17.5kVA

50Hz

Control System

Deepsea (UK)	Model	DSE4620
Protection	Parameter	
<ul style="list-style-type: none"> ■ Low oil pressure ■ High water temp ■ Over speed ■ Over crank ■ Over load ■ Over/low volt ■ Over/low frequency ■ Battery charge failure 	<ul style="list-style-type: none"> ■ Volt ■ current ■ power ■ speed ■ frequency 	<ul style="list-style-type: none"> ■ oil pressure ■ oil temp ■ power factor ■ running time ■ water temp ■ battery voltage
		

Option

External ATS



Water Heater



Oil Heater



Paralleling System

